



# **K SYSTEMS**

## **Technical Information Sheet**

### *Product Data Sheet*

## **MA40**

<b>Series:</b>	<b>MA40</b>
<b>Description:</b>	Metallized foils for use in the omnicrom system, toner reactive applications, and specific plastics applications such as low and high density polyethylene and PVC.
<b>Release Characteristic:</b>	Medium
<b>Coverage:</b>	Fine to Medium
<b>Application Temperature:</b>	250 - 350°F 120 - 175°C
<b>Carrier:</b>	E-film: 12 Micron (48 gauge) clear polyester film
<b>Shelf Life:</b>	about 3 years if stored at 70 - 80°F, 50%RH

*Not all series are standard products for each color. Please contact our Sales Service Department for questions about standard products. The information herein is based on scientific data available to us and is presented in good faith. The values presented are intended only as a source of information and given without guarantee and do not constitute a warranty. Since the conditions under which this information may be applied are beyond our control, we can assume no liability for the results of the application. Purchasers should independently determine, prior to use, the suitability of this material for their specific application. No warranty, expressed or implied, is given.*

**34 Betty Street, Jeppestown, Johannesburg**  
**Tel: (011) 618-3304/5/6**  
**Fax: (011) 624-3102**  
**E-mail: [info@k-systems.co.za](mailto:info@k-systems.co.za)**

-----  
All K SYSTEMS products have been developed for a particular range of applications. However, experience shows that substrates, printing equipment and operating conditions can vary, and users of our products are urged to verify, by means of test printing, that particular grades are appropriate for their specific applications. For this purpose, test samples are available on request. If you need help, K SYSTEMS will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.